

CLAIMS

I claim:

1. A mailbox assembly including:
a housing including a bottom wall, a first side wall, a second side wall, and a back wall, a front wall being hingedly coupled to said housing and defining a first door for selectively opening or closing said housing, a top wall being attached to said first and second side walls, said top wall being substantially transparent;
a window being positioned in said first side wall, said window comprising a substantially transparent material, said window having a pair of apertures extending therethrough; and
a pair of gloves each having a wrist portion and a hand portion, each of said wrist portions being attached to and extending along a perimeter edge of one of said apertures such that each of said gloves extend into housing.
2. The assembly of claim 1, further including a cover being hingedly coupled to said housing and being selectively positionable in a closed position covering said top wall.
3. The assembly of claim 1, wherein each of said gloves comprising an elastomeric material.
4. The assembly of claim 2, further including a second door being hingedly coupled to said housing, said second door being selectively positionable in a closed position covering said window.

5. The assembly of claim 1, further including a second door being hingedly coupled to said housing, said second door being selectively positionable in a closed position covering said window.

6. The assembly of claim 4, further including a securing member being attached to said second door and said cover for selectively securing said second door and said cover in said closed positions.

7. The assembly of claim 1, further including a bracket being attached to said bottom wall for selectively attaching said housing to a post.

8. The assembly of claim 4, further including a handle being attached to and extending upwardly from said cover.

9. A mailbox assembly including:

a housing including a bottom wall, a first side wall, a second side wall, and a back wall, a front wall being hingedly coupled to said housing and defining a first door for selectively opening or closing said housing, a top wall being attached to said first and second side walls, said top wall being substantially transparent;

a cover being hingedly coupled to said housing and being selectively positionable in a closed position covering said top wall;

a window being positioned in said first side wall, said window comprising a substantially transparent material, said window having a pair of apertures extending therethrough;

a pair of gloves each having a wrist portion and a hand portion, each of said wrist portions being attached to and extending along a perimeter edge of one of said apertures such that each of said

gloves extend into housing, each of said gloves comprising an elastomeric material;

a second door being hingedly coupled to said housing, said second door being selectively positionable in a closed position covering said window;

a securing member being attached to said second door and said cover for selectively securing said second door and said cover in said closed positions;

a bracket being attached to said bottom wall for selectively attaching said housing to a post; and

a handle being attached to and extending upwardly from said cover.